

FLC

DESCRIPTION:

FLC is a very strong, heavy-duty, high-foaming, liquid caustic cleaner designed for use in the meat processing and other food processing industries where caustic foam cleaning is performed. **FLC** is especially effective in cleaning smoke houses, loading docks, fillers, inspection belts, moving tables, kill floors, cutters, and other food processing equipment suitable for caustic foam cleaning. Organic residues such as grease, fats, blood, and tissues are quickly emulsified and rinsed free from surfaces.

PROPERTIES

- Color— A dark brown colored liquid
- Form—A viscous, heavy liquid.
- Foam—A VERY HIGH foaming blend; stable foam
- Rinsing—Easy and complete rinsing properties
- Solubility—Complete. May require some agitation
- Emulsifying power—Swift, complete and powerful saponification and emulsification power

OPERATING DATA

EQUIPMENT: Use **FLC** with existing or new foam generation equipment.

CONCENTRATION: Typically **FLC** is used between 4-8 ounces per gallon of water. Soil load and conditions will indicate proper dilutions level (32-64 mls per liter). Be sure **FLC** is thoroughly dissolved/dispersed before using. **FLC** is a heavy, dense, viscous liquid that may require agitation for thorough dissolution. Stronger solutions may be used for extra heavy duty cleaning action.

TEMPERATURE: Ambient to 120°F/49°C

BASIC INSTRUCTIONS: Pre-rinse to remove gross, loose soils. Apply a thick blanket of foam and allow to “eat” into soils for 10-15 minutes. **DO NOT ALLOW FOAM TO DRY.** Rinse well and sanitize if desired.

SAFETY

FLC contains sodium hydroxide. **PLEASE use ALL appropriate safety gear and PPE when handling and working with this product.** PLEASE thoroughly read MSDS prior to use. Rubber gloves, boots, apron, and face shield are recommended. A respirator may be needed in enclosed areas. Avoid contact with eyes, skin, or mucous membranes. **FLC** is USDA approved for use on food contact surfaces.

CONTAINERS

Available in drums, totes, and bulk. Special packaging upon request.



MANUFACTURED BY:



6601 Northway
Greendale, WI 53129
(414)-858-2300
Fax (414)-858-2310
bmofoffatt@camcochemical.com
www.camcochemical.com

DISTRIBUTED BY: